SAFETY DATA SHEET



ACE 204 Epoxy Primer A-Component

Section 1. Identification

GHS product identifier	: ACE 204 Epoxy Primer A-Component
Product code	: Not available.
Other means of identification	: Not available.
Product type	: Liquid.

Relevant identified uses of the substance or mixture and uses advised against

: Ace Epoxy

Identified uses

Concrete Floor Primer Coating Epoxy Blend.

Supplier's details

	Gi T€ Er	051 Mustang Drive, Suite 200 rapevine, TX 76051 el.: (682) 337-0400 mail: sales@aceepoxy.com debsite: www.aceepoxy.com	
Emergency telephone number (with hours of operation)		foTrac: 1-800-535-5053 :00 a.m. – 5:00 p.m. PST)	

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2 AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2
GHS label elements Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H361 - Suspected of damaging fertility or the unborn child. H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Section 2. Hazards identification

Prevention	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P280 - Wear protective gloves, protective clothing and eye or face protection.
	P273 - Avoid release to the environment. P261 - Avoid breathing vapor.
	P264 - Wash thoroughly after handling.
	P272 - Contaminated work clothing must not be allowed out of the workplace.
Response	: P391 - Collect spillage.
	P308 + P313 - IF exposed or concerned: Get medical advice or attention.
	P362 + P364 - Take off contaminated clothing and wash it before reuse.
	P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.
	P302 + P302 - If Skin irritation or rash occurs: Get medical advice or attention.
	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: P405 - Store locked up.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

Ingredient name	%	CAS number
bis-[4-(2,3-Epoxipropoxi)phenyl]propane	≥50 - ≤75	1675-54-3
Limestone	≥10 - ≤25	1317-65-3
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs.	≥10 - ≤25	68609-97-2
4-Nonylphenol, Branched	≥1 - <2.5	84852-15-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary fi	irst ai	<u>d measures</u>
Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First aid measures

Skin contact	: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact :	Causes serious eye irritation.	
Inhalation	No known significant effects or critical hazards.	
Skin contact	Causes skin irritation. May cause an allergic skin reaction.	
Ingestion	No known significant effects or critical hazards.	
Over-exposure signs/symptoms		
Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact :	Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion :	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- diodital production protoc	
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ontainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	t on appropriate personal protective equipment (see Section 8). Persons w tory of skin sensitization problems should not be employed in any process i s product is used. Avoid exposure - obtain special instructions before use. cosure during pregnancy. Do not handle until all safety precautions have be d understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid eathing vapor or mist. Avoid release to the environment. If during normal u aterial presents a respiratory hazard, use only with adequate ventilation or w propriate respirator. Keep in the original container or an approved alternative m a compatible material, kept tightly closed when not in use. Empty contain oduct residue and can be hazardous. Do not reuse container.	n which Avoid een read oid se the ear ve made
Advice on general occupational hygiene	ting, drinking and smoking should be prohibited in areas where this materia ndled, stored and processed. Workers should wash hands and face before nking and smoking. See also Section 8 for additional information on hygien easures.	eating,
Conditions for safe storage, including any incompatibilities	bre between the following temperatures: 15 to 35°C (59 to 95°F). Store in cordance with local regulations. Store in original container protected from d nlight in a dry, cool and well-ventilated area, away from incompatible materia ction 10) and food and drink. Store locked up. Keep container tightly close aled until ready for use. Containers that have been opened must be careful sealed and kept upright to prevent leakage. Do not store in unlabeled conta e appropriate containment to avoid environmental contamination. See Sec compatible materials before handling or use.	als (see d and ly iners.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
bis-[4-(2,3-Epoxipropoxi)phenyl]propane Limestone	None. OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs. 4-Nonylphenol, Branched	None.

Appropriate engineering controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid. [Viscous. Translucent.]
Color	: Water white.
Odor	: Mild aromatic.
Odor threshold	: Not available.
рН	: Not available.
Melting/freezing point	: Not available.
Initial boiling point and	: >260°C (>500°F)
boiling range	
Flash point	: Closed cup: 252°C (485.6°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive	: Not available.
(flammable) limits	
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: 1.114
Solubility	: Not available.
Solubility in water	: Not available.

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com



Section 9. Physical and chemical properties

Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Dynamic (room temperature): 2000 to 3000 mPa⋅s (2000 to 3000 cP)
Flow time (ISO 2431)	1	Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid high temperatures.
Incompatible materials	: Reactive or incompatible with the following materials: reactive metals and hydroxyl containing compounds.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
bis-[4-(2,3-Epoxipropoxi) phenyl]propane	LD50 Dermal	Rabbit	20 g/kg	-
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs.	LD50 Oral	Rat	17100 mg/kg	-
4-Nonylphenol, Branched	LD50 Oral	Rat	1300 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
bis-[4-(2,3-Epoxipropoxi) phenyl]propane	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs.	Skin - Moderate irritant	Rabbit	-	24 hours 500 μL	-
4-Nonylphenol, Branched	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 mg	-

Sensitization

There is no data available.

Mutagenicity

Section 11. Toxicological information

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
bis-[4-(2,3-Epoxipropoxi) phenyl]propane	-	3	-

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely	:	Routes of entry anticipated:	Oral, Dermal.
routes of exposure			

Potential acute health effects

Eye contact	1	Causes serious eye irritation.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes skin irritation. May cause an allergic skin reaction.
Ingestion	1	No known significant effects or critical hazards.

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations



Section 11. Toxicological information

Delayed and immediate effe	cts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
<u>Long term exposure</u>	
Potential immediate effects	: No known significant effects or critical hazards.
Potential delayed effects	: No known significant effects or critical hazards.
Potential chronic health eff	<u>ects</u>
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
ACE 204 Epoxy Primer A-Component	87248.3		N/A	N/A	N/A
bis-[4-(2,3-Epoxipropoxi)phenyl]propane	N/A		N/A	N/A	N/A
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs.	17100		N/A	N/A	N/A
4-Nonylphenol, Branched	1300		N/A	N/A	N/A

Section 12. Ecological information

Toxicity Product/ingredient name Result **Species Exposure** 4-Nonylphenol, Branched 72 hours Acute EC50 0.03 mg/L Marine water Algae - Skeletonema costatum Acute EC50 0.027 mg/L Marine water Algae - Skeletonema costatum 96 hours Acute EC50 137 µg/L Marine water Crustaceans - Eohaustorius 48 hours estuarius - Adult Acute LC50 17 µg/L Marine water Fish - Pleuronectes americanus -96 hours Larvae Chronic EC10 0.012 mg/L Marine water Algae - Skeletonema costatum 96 hours Chronic NOEC 5 µg/L Fresh water Crustaceans - Gammarus 21 days fossarum - Adult Fish - Pimephales promelas -33 days Chronic NOEC 7.4 µg/L Fresh water Embryo

Persistence and degradability

There is no data available.

Bioaccumulative potential





ACE 204 Epoxy Primer A-Component

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
Oxirane, Mono[(C12-14-Alkyloxy)Methyl] Derivs.	3.77	160 to 263	low
4-Nonylphenol, Branched	5.4	740	high

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-Nonylphenol, Branched)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-Nonylphenol, Branched)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4-Nonylphenol, Branched)
Transport hazard class(es)	9	9	9
Packing group		Ш	
Environmental hazards	Yes.	Yes.	Yes.

Additional information DOT Classification

: Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

AERG : 171

Section 14. Transport information

IMDG	-	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
ΙΑΤΑ	:	This product is not regulated as a dangerous good when transported in sizes of \leq 5 L or \leq 5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.
Special precautions for user	:	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to IMO instruments	:	Not available.

Section 15. Regulatory information

U.S. Federal regulations	: TSCA 5(a)2 final significant new use rules: 4-Nonylphenol, Branched
	TSCA 8(a) PAIR : 4-Nonylphenol, Branched; 2-Methoxy-1-methylethyl acetate; Naphthalene
	TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	TSCA 12(b) one-time export: 4-Nonylphenol, Branched
	Clean Water Act (CWA) 307: Ethylbenzene; Benzene; Naphthalene; Toluene
	Clean Water Act (CWA) 311: Xylene; Ethylbenzene; Benzene; Naphthalene; Toluene
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed
SARA 302/304	
Composition/information	<u>i on ingredients</u>
No products were found.	
SARA 304 RQ	: Not applicable.
SARA 311/312	
Classification	 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 TOXIC TO REPRODUCTION - Category 2
Composition/information	on ingradients

Composition/information on ingredients

Section 15. Regulatory information

Name	%	Classification
bis-[4-(2,3-Epoxipropoxi)phenyl] propane		FLAMMABLE LIQUIDS - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
Oxirane, Mono[(C12-14-Alkyloxy) Methyl] Derivs.	≥10 - ≤25	SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1
4-Nonylphenol, Branched	≥1 - <2.5	ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 TOXIC TO REPRODUCTION - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	4-Nonylphenol, Branched	84852-15-3	≥1 - <2.5
Supplier notification	4-Nonylphenol, Branched	84852-15-3	≥1 - <2.5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: Limestone
New York	: None of the components are listed.
New Jersey	: The following components are listed: Limestone
Pennsylvania	: The following components are listed: Limestone
California Prop. 65	

▲ WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Crystalline silica, respirable powder, Cumene, Ethylbenzene and Naphthalene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Crystalline silica, respirable powder	-	-
Cumene	-	-
Ethylbenzene	Yes.	-
Benzene	Yes.	Yes.
Naphthalene	Yes.	-
Toluene	-	Yes.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 15. Regulatory information

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

United States (TSCA 8b)

All components are active or exempted.

Section 16. Other information

Procedure used to derive the classification

	Classification	Justification
SKIN CORROSION/IRRITA SERIOUS EYE DAMAGE/ E SKIN SENSITIZATION - Ca TOXIC TO REPRODUCTIO AQUATIC HAZARD (ACUTE AQUATIC HAZARD (LONG	YE IRRITATION - Category 2A tegory 1 N - Category 2 E) - Category 2	Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method
<u>History</u>		
Date of issue/Date of revision	: 03/15/2021	
Date of previous issue	: Not applicable	
Version	: 1	
Prepared by	: KMK Regulatory Services Inc.	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

