# SAFETY DATA SHEET



### **ACE 204 Epoxy Primer B-Component**

### **Section 1. Identification**

GHS product identifier : ACE 204 Epoxy Primer B-Component

Product code : Not available.

Other means of : Not available.
identification

Product type : Liquid.

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

Concrete Floor Primer Coating Cycloaliphatic Amine Adduct.

Supplier's details : Ace Epoxy

1051 Mustang Drive, Suite 200

Grapevine, TX 76051 Tel.: (682) 337-0400

Email: sales@aceepoxy.com Website: www.aceepoxy.com

Emergency telephone number (with hours of operation) : InfoTrac: 1-800-535-5053 (8:00 a.m. – 5:00 p.m. PST)

### Section 2. Hazards identification

#### **OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

# Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

#### **GHS label elements**

Hazard pictograms









Signal word : Danger



### Section 2. Hazards identification

**Hazard statements** : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H341 - Suspected of causing genetic defects. H360 - May damage fertility or the unborn child.

H370 - Causes damage to organs.

H372 - Causes damage to organs through prolonged or repeated exposure.

H410 - Very toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

**Prevention**: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

P260 - Do not breathe vapor.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace.

Response : P391 - Collect spillage.

P308 + P311 - IF exposed: Call a POISON CENTER or doctor.

P304 + P340, P310 - IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER or doctor.

P301 + P310, P330, P331 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353, P310 - IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or

doctor.

P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor.

Storage : P405 - Store locked up.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

classified

: None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : Not available.

identification

Ingredient name	%	CAS number
3-Aminomethyl-3,5,5-Trimethylcyclohexylamine	≥25 - ≤50	2855-13-2
Aliphatic amine	≥25 - ≤50	-
Amine-Epoxy Adduct	≥10 - ≤25	-
Benzyl alcohol	≥10 - ≤25	100-51-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.





## Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Eye contact** 

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Skin contact** 

Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Causes damage to organs following a single exposure if inhaled.

Skin contact : Causes severe burns. Causes damage to organs following a single exposure in contact

with skin. May cause an allergic skin reaction.

**Ingestion**: Causes damage to organs following a single exposure if swallowed.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations





### Section 4. First aid measures

Skin contact

: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion

: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

**Unsuitable extinguishing** media

: Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous thermal** decomposition products Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.





## Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 15 to 35°C (59 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
3-Aminomethyl-3,5,5-Trimethylcyclohexylamine Aliphatic amine	None.  ACGIH TLV (United States).  TWA: 0.1 mg/m³  OSHA PEL (United States).  TWA: 0.1 mg/m³  NIOSH REL (United States).  TWA: 0.1 mg/m³
Amine-Epoxy Adduct Benzyl alcohol	None.  AIHA WEEL (United States, 7/2018).  TWA: 10 ppm 8 hours.

#### Appropriate engineering controls

#### **Environmental exposure** controls

- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### **Skin protection** Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.





## Section 8. Exposure controls/personal protection

Body protection : Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Respiratory protection**: Based on the hazard and potential for exposure, select a respirator that meets the

appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important

aspects of use.

## Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Clear.]

Color : Straw.
Odor : Amine.

Odor threshold : Not available.

PH : Not available.

Melting/freezing point : Not available.

Initial boiling point and : 207°C (404.6°F)

boiling range

Flash point : Closed cup: 110°C (230°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : <1.4 kPa (<10.37 mm Hg) [room temperature]

Vapor density : Not available.

Relative density : 0.97

Solubility : Not available.

Solubility in water : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): 100 to 300 mPa·s (100 to 300 cP)

Flow time (ISO 2431) : Not available.

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.





# Section 10. Stability and reactivity

**Conditions to avoid** 

: Avoid high temperatures.

**Incompatible materials** 

: Reactive or incompatible with the following materials: reactive metals and hydroxyl containing compounds.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **Section 11. Toxicological information**

### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Aliphatic amine	LC50 Inhalation Dusts and mists		2.4 mg/L	4 hours
	LD50 Oral		1040 mg/kg	-
Benzyl alcohol	LD50 Dermal LD50 Oral		2000 mg/kg 1230 mg/kg	-

#### **Irritation/Corrosion**

There is no data available.

#### **Sensitization**

There is no data available.

#### **Mutagenicity**

There is no data available.

#### **Carcinogenicity**

There is no data available.

#### Reproductive toxicity

There is no data available.

#### **Teratogenicity**

There is no data available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
Amine-Epoxy Adduct	Category 1	-	-

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Amine-Epoxy Adduct	Category 1	-	-

#### **Aspiration hazard**

There is no data available.

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects





## **Section 11. Toxicological information**

**Eye contact** : Causes serious eye damage.

Inhalation : Causes damage to organs following a single exposure if inhaled.

**Skin contact**: Causes severe burns. Causes damage to organs following a single exposure in contact

with skin. May cause an allergic skin reaction.

Ingestion : Causes damage to organs following a single exposure if swallowed.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion** : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

**Long term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a

severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity**: No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.Reproductive toxicity : May damage fertility or the unborn child.

### Numerical measures of toxicity

**Acute toxicity estimates** 





## **Section 11. Toxicological information**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	(gases)	(vapors)	Inhalation (dusts and mists) (mg/ I)
3-Aminomethyl-3,5,5-Trimethylcyclohexylamine	500	1100	N/A	N/A	N/A
Aliphatic amine	1040	N/A	N/A	N/A	2.4
Benzyl alcohol	1230	N/A	N/A	N/A	1.5

## **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
3-Aminomethyl- 3,5,5-Trimethylcyclohexylamine	Acute EC50 17.4 mg/L Fresh water	Daphnia - Daphnia magna	48 hours
Benzyl alcohol		Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
3-Aminomethyl- 3,5,5-Trimethylcyclohexylamine	0.99	-	low
Benzyl alcohol	0.87	-	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.





# **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	UN2735	UN2735	UN2735
UN proper shipping name	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-Aminomethyl- 3,5,5-Trimethylcyclohexylamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-Aminomethyl- 3,5,5-Trimethylcyclohexylamine)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-Aminomethyl- 3,5,5-Trimethylcyclohexylamine)
Transport hazard class(es)	8 CORROLL TO THE PARTY OF THE P	8	8
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes. The environmentally hazardous substance mark is not required.

**AERG** : 153

**Additional information** 

**DOT Classification** : This product is not regulated as a marine pollutant when transported on inland

waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. **IMDG** 

The environmentally hazardous substance mark may appear if required by other

transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

**IATA** 

## **Section 15. Regulatory information**

**U.S. Federal regulations** : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

**Clean Air Act Section 112** 

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances

: Not listed

**DEA List I Chemicals** (Precursor Chemicals)

**DEA List II Chemicals** (Essential Chemicals) : Not listed





## **Section 15. Regulatory information**

#### **SARA 302/304**

#### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : SKIN CORROSION/IRRITATION - Category 1C

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1

GERM CELL MUTAGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

#### **Composition/information on ingredients**

Name	%	Classification
3-Aminomethyl-	≥25 - ≤50	ACUTE TOXICITY (oral) - Category 4
3,5,5-Trimethylcyclohexylamine		ACUTE TOXICITY (dermal) - Category 4
		SKIN CORROSION/IRRITATION - Category 1B
		SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
		SKIN SENSITIZATION - Category 1
Aliphatic amine	≥25 - ≤50	ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (inhalation) - Category 4
Amine-Epoxy Adduct	≥10 - ≤25	GERM CELL MUTAGENICITY - Category 2
		TOXIC TO REPRODUCTION - Category 1B
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) -
		Category 1
		SPECIFIC TARGET ORGAN TOXICITY (REPEATED
		EXPOSURE) - Category 1
Benzyl alcohol	≥10 - ≤25	ACUTE TOXICITY (oral) - Category 4
		ACUTE TOXICITY (inhalation) - Category 4

#### **State regulations**

Massachusetts : The following components are listed: Benzyl alcohol

**New York**: None of the components are listed.

New Jersey : The following components are listed: 3-Aminomethyl-3,5,5-Trimethylcyclohexylamine

Pennsylvania : The following components are listed: Benzyl alcohol

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

#### **International regulations**

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.





## **Section 15. Regulatory information**

**UNECE Aarhus Protocol on POPs and Heavy Metals** 

Not listed.

**Inventory list** 

United States (TSCA 8b) : All components are active or exempted.

### Section 16. Other information

#### Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1C	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
GERM CELL MUTAGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

#### **History**

Date of issue/Date of

revision

Date of previous issue : Not applicable

Version :

Prepared by : KMK Regulatory Services Inc.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

: 03/15/2021

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group

UN = United Nations

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

